

Technical Data Sheet QP SEMI-SYNTHETIC ENGINE OIL SAE 10W 40

API: SL / CI-4

Description

QP SEMI-SYNTHETIC 10W 40 is an engine oil blended from semi-synthetic base oils, which has been fortified with High performance additives including the unique synthetic ester blend to provide unsurpassed long life performance which meets API: SL/CI-4 specification and associated OEM approvals.

Outstanding Features

QP SEMI-SYNTHETIC 10W 40, API: SL/CI-4 meets or exceeds the following specifications:

- API SL/CI-4
- ACEA A3/B4
- MB 229.1

Directions for Use

QP SEMI-SYNTHETIC 10W 40, API: SL/CI-4 oils are recommended for naturally-aspirated and turbo charged diesel engines and petrol engines calling for API classification SL & CI-4. They can also be used in a variety of other industrial applications, such as certain types of compressors where the manufacturer specifies the use of engine oil. They can also be used in mixed fleet operations and forklifts, high performance, highly stressed engines whether on-road or off-road vehicles etc.

Technical Data

SAE grade	10W 40
Viscosity @ 40°C	87
Viscosity @ 100°C	13.66
Viscosity Index	160
Pour Point °C	-33
Flash Point	224

Pack Sizes

210 Lt Drum 20 Lt Pail 5 Lt Bottle