



SUPER TRACTOR OIL UNIVERSAL - SAE 15W 40
API: SF/CG-4
QP MULTI-PURPOSE TRACTOR OIL (STOU)

Description

SUPER TRACTOR 15W 40 is a multipurpose oil designed for use in farm tractors. It is blended from virgin base oils which have been fortified with anti-wear, anti-oxidant, anti-foam and anti-corrosion inhibitors together with viscosity index improvers. It is suitable for use in the engine, transmission, final drive and hydraulics of tractors. The additives used provide smooth and quiet operation of wet brakes and PTO clutches.

Outstanding Features

SUPER TRACTOR 15W 40 meets or exceeds the following specifications:

- API SF/CG-4
- API GL-4
- John Deere JDM 27 (approved additives)
- Mack EO-K2
- Ford ESN-M2C-159C

Specifications

SUPER TRACTOR 15W 40 is manufactured with John Deere approved additive: Chevron Oronite.

Application

SUPER TRACTOR 15W 40 is suitable for use in all engines, transmissions, final drives and hydraulics of farm tractors. The blend of additives used provides excellent protection against wear and corrosion, while at the same time having an effective “anti-squawk” property.

Technical Data

SAE grade	15W 40
Viscosity @ 40	120 Viscosity
@ 100	14.8
Viscosity Index	120
Pour Point	-28

Pack Sizes

210L	Drum
20L	Pail
5L	Bottle