



QUALIPRO LUBRICANTS

Protect - Clean - Cool

QP Engine SAE 15W 40.

API :- SL / CI-4 PLUS

Description

QP Engine 15W 40 is an engine oil blended from highly refined Group II base oils, which has been fortified with High performance additives including the "TRUE-SYN" unique synthetic ester blend to provide unsurpassed long life performance which meets API: SL/CI-4 specification and associated OEM approvals.

Outstanding Features

QP Engine 15W 40, API: SL/CI-4 PLUS meets or exceeds the following specifications:

• API:-	SL/CI-4 PLUS
• ACEA	E7-08, E5-02, E3-96
• CUMMINS	20078 , 20077, 20076, 20072
• MB	228.3
• VOLVO	VDS 3
• MACK	EO-N PREMIUM PLUS 03, EO-M PLUS
• MAN	3275
• MTU	CATEGORY 2
• CAT	ECF-2 , ECF-1-a

Directions for Use

QP Engine 15W 40, API: SL/CI-4 PLUS oils are recommended for naturally-aspirated and turbo charged diesel engines and petrol engines calling for API classification SL & CI-4 PLUS.

Specifically designed for the latest electronically controlled diesel engines, including those fitted with EGR and / or SCR systems. Formulated with TRUE SYN technology to deliver exceptional soot dispersancy, deposit control and wear protection.

QP Engine 15W 40 can also be used in a variety of other agricultural and industrial applications, such as certain types of generators where the manufacturer specifies the use of top tier engine oil and also for mixed fleet operations, forklifts, etc.

TRUE - SYN - ADDED



QUALIPRO LUBRICANTS

Protect - Clean - Cool

Technical Data

SAE grade	15W 40
Density at 15°C, kg/L	0.886
Base No. D2896, mg KOH/g	12.2
Base No. D4739, mg KOH/g	10.1
Flash Point °C	230
Phosphorus, m%	0.13
Sulfated Ash, m%	1.4
Zinc, m%	0.15
Viscosity @ 40°C	125
Viscosity @ 100°C	15.1
Viscosity Index	125
Pour Point °C	-35

Pack Sizes

1000 lt Bulk bins
210 Lts Drum
20 Lts Bottle
5 Lts Bottle