


QUALIPRO LUBRICANTS

Protect - Clean - Cool

QP SYNTHETIC ENGINE OIL SAE 5W 30.

API :- SL / CI-4.

Description

QP SYNTHETIC 5W 30 is an engine oil blended from synthetic base oils, which has been fortified with High performance additives including the "TRUE-SYN" unique synthetic ester blend to provide unsurpassed long life performance which meets API: SL/CI-4 specification and associated OEM approvals.

Outstanding Features

QP SYNTHETIC 5W 30, API: SL/CI-4 PLUS meets or exceeds the following specifications:

- API SL/CI-4 PLUS
- ACEA E5-2002
- MB 229.51
- VOLVO VDS 2
- MACK EOM PLUS
- MAN 3275

Directions for Use

QP SYNTHETIC 5W 30, API: SL/CI-4 oils are recommended for naturally-aspirated and turbo charged diesel engines and petrol engines calling for API classification SL & CI-4 PLUS. They can also be used in a variety of other industrial applications, such as certain types of compressors where the manufacturer specifies the use of engine oil. They can also be used in mixed fleet operations and forklifts, etc.

Technical Data

SAE grade	5W 30
Viscosity @ 40°C	55
Viscosity @ 100°C	9.8
Viscosity Index	162
Pour Point °C	-35

Pack Sizes

210 Lts Drum
20 Lts Pail
5 Lts Bottle

**T
R
U
E
-
S
Y
N
-
A
D
D
E
D**